

16.810
Vehicle Design Summit Team 1
Ingress/Egress



Design System

Analysis and Optimization

Fabrication

Design System

Objective :

Multi-Objective problem

Quantifiable Criteria

Cost (\$)

Visibility (sq. m)

Egress Ingress (sec)

Unquantifiable Criteria

Ease of Manufacturability

Aesthetics

Design System

Analysis and Optimization

Fabrication

Design System

Constraints:

Shape of existing Shell (m)

Weight (Kg)

Cost (\$)

Design Variables:

Geometry (Number and positions of Joints)

Material (Transparency/Opaque)

Kinematics (Hinge, Slider..etc)


Design System

Analysis and Optimization

Fabrication

Design System

Concept




Design System

Analysis and Optimization


Fabrication

□ Design System

AHPV Design Space



Design Solution Tree:





Design System

Analysis and Optimization

Fabrication

Design System




Design System

Analysis and Optimization

Fabrication

Design System




Design System

Analysis and Optimization

Fabrication

Design System




Design System

Analysis and Optimization

Fabrication

Design System



Design System

Analysis and Optimization

Fabrication

Design System




Design System

Analysis and Optimization

Fabrication

Design System




Design System

Analysis and Optimization

Fabrication

Design System



Design System




Analysis and Optimization

Fabrication

Analysis and Optimization

Test 1 – ‘Hard Opening’

- Highest dynamic load when someone opens canopy and pins hit end of rails
- Force of $2g$ * mass of canopy ~ 11 pounds
- Restraints of fixed edges roughly equivalent to final design
- Stress concentrated around joint
- Displacements acceptable



Design System



Analysis and Optimization

Fabrication

□ Analysis and Optimization

Test 2 – ‘Driving Pressure Force’

- Pressure on canopy while driving 60mph $\sim 550\text{N/m}^2$
- Restraints of fixed edges based on magnetic strips
- Natural modes at low freq – first mode at 0.5Hz
- Canopy displacement $\sim 3\text{mm}$ max at 60mph



List Modes

Study name: Canopy-Vibration

Mode No.	Frequency(Rad/sec)	Frequency(Hertz)	Period(Seconds)
1	3.5625	0.56539	1.7697
2	22.261	3.543	0.28225
3	47.948	7.6311	0.13104
4	62.372	9.8303	0.10074
5	122.38	19.477	0.051343

Close Save Help

Design System

Analysis and Optimization

Fabrication


Analysis and Optimization

Test 3 – ‘Rail Optimization’

- Varied thickness of rail to find optimum size to avoid yield at min mass
- Force of 40N side load – someone leaning on canopy

Thickness (inches)	FoS
1	8.9
0.5	2.7
0.25	2.0

- We tried to use a thicker sandwich material – delaminated
- Now using 0.25 inch aluminium, slightly different rail design





Design System

Analysis and Optimization

Fabrication

Analysis and Optimization




Design System

Analysis and Optimization

Fabrication

Analysis and Optimization



Design System

Analysis and Optimization

Fabrication

Fabrication

Canopy – Ordered from professional manufacturer in Florida
Handles – Aluminium tube welded onto waterjetted guide rails
Rails – Aluminium, waterjet, attached by U-Clamp
Attachment – Adhesive backed magnetic strip

Design System

Analysis and Optimization

Fabrication

Fabrication



Design System

Analysis and Optimization

Fabrication

Fabrication



Design System

Analysis and Optimization

Fabrication

Fabrication



Design System

Analysis and Optimization

Fabrication

Fabrication



Design System

Analysis and Optimization

Fabrication

Fabrication



Design System

Analysis and Optimization

Fabrication

Fabrication



Design System

Analysis and Optimization

Fabrication

Fabrication

What's Next...?

- Handles welded to rails
- Attach rail to chassis
- Sand shell and canopy
- Reinforcing canopy
- Attaching canopy to reinforcement
- Attaching reinforced canopy to handles
- Test mechanism, fix problems!
- Stick on magnetic strips so canopy stays shut
- Drive AHPV to Solidworks World
- Sleep...

Cost Estimation

**16.810 Cost Estimation Sheet
Team V1**

Section		Rate	Qty	Cost	
<i>I. Design and Engineering</i>					
	Labor Rate for Each Designer	\$75	10	\$750	
	Labor Rate for Each CAD/CAM Workstation	\$40	5	\$200	
<i>II. Materials Cost</i>					
	Aluminium Sheet	1/16" thick	\$40	1	\$40
		1/4" thick	\$80	1	\$80
	Aluminium Tube		\$20	1	\$20
	Miscellaneous Components		\$60	1	\$60
<i>III. Canopy</i>					
	Canopy		\$350	1	\$350
	Shipping		\$200	1	\$200
<i>IV. Waterjet Manufacturing</i>					
	Labor Rate		\$55	3	\$165
	Machine Use		\$75	3	\$225
<i>V. Other Manufacturing</i>					
	Shell and Canopy Cutting - Labor		\$40	4	\$160
	Miscellaneous Labor		\$30	8	\$240
<i>VI. Assembly and Testing</i>					
	Assembly Labor		\$30	3	\$90
			TOTAL	\$2,580	


Design System

Analysis and Optimization

Fabrication

Lessons Learned

- Set realistic goals
- Better use of FEA for optimization – our rail could have been designed to be lighter
- Start manufacturing early, maybe finish on time
- Have the right tools
- Make the right decisions at the right time



To be continued...

Design System

Analysis and Optimization

Fabrication