

software studio

intro to the DOM

Daniel Jackson

what is the DOM?

an API for manipulating web pages

- › elements are mutable objects

what you can do

- › add and delete elements
- › change properties of elements
- › attach event listeners to elements

what you can't do

- › modify CSS rules: no CSS rule object in DOM
- › but can modify CSS properties of elements
- › and new CSS object model in works...

page elements

The new, faster MacBook Air

The ultimate everyday notebook.
Now up to 2.5x faster, featuring high-speed Thunderbolt I/O and OS X Lion.

div#billboard [680x400]

OS X Lion. Available Now.
Download it today from the Mac App Store.

Watch the new iPad TV ad.

iCloud. Coming this fall.
iCloud stores your content and wirelessly pushes it to all your devices.

Buy a Mac for college
and get \$100 to spend
on the Mac App Store.
Terms apply.

Shop the [Apple Online Store](#) (1-800-MY-APPLE), visit an [Apple Retail Store](#), or find a [reseller](#).
[Site Map](#) | [Hot News](#) | [RSS Feeds](#) | [Media Info](#) | [Environment](#) | [Job Opportunities](#) | [Contact Us](#)

```
 lang="en-US">
> <head>...</head>
<body id="home" class="keynote">
  <script type="text/javascript">
    var searchSection = 'global';
    var searchCountry = 'us';
  </script>
  <script src="http://images.apple.com/globalnav.js" type="text/javascript" 8"></script>
  <nav id="globalheader" class="apple g globalheader-loaded globalheader-load <script type="text/javascript"> AC.GlobalNav.Instance = new A </script>
  <div id="globalheader-loaded-test"></div>
  <div id="top">...</div>
  <div id="main">
    <div id="content">
      <div id="billboard">...</div>
      <!--/billboard-->
      <aside id="headlines">...</aside>
      <aside class="promos">...</aside>
      <!--/promos-->
    </div>
    <!--/content-->
    <footer id="homefooter">...</footer>
    <!--/homefooter-->
  </div>
  <!--/main-->
  <!-- Start of DoubleClick Spotlight Tag remove-->
  <!-- Creation Date:11/19/07 -->
  <script type="text/javascript">...</script>
  <iframe src="http://fls.doubleclick.net/src=1566767;type=apple663;cat=apple24 ord=6378379939123.988?" width="1" height="0">...</iframe>
  <noscript>...</noscript>
  <!-- End of DoubleClick Spotlight Tag remove-->
</body>
</html>
```

the standard DOM

standard DOM API

- › standardized by W3C
- › native to all browsers

Gecko documentation

- › Mozilla's layout engine
- › comprehensive docs

Methods

Properties

Name	Description	Type
attributes	All attributes associated with an element.	NamedNodeMap
baseURI	Base URI as a string	String
baseURIObject <small>New in Firefox 3</small>	The read-only nsIURI object representing the base URI for the element.	nsIURI
childElementCount <small>New in Firefox 3.5</small>	The number of child nodes that are elements.	Number
childNodes	All child nodes of an element. A live nsIDOMNodeList of the current child elements.	NodeList
children <small>Requires Gecko 1.9</small>	All child nodes of an element as a collection.	HTMLCollection
classList <small>Requires Gecko 1.9.2</small>	Token list of class attribute	DOMTokenList
className	Gets/sets the class of the element.	String

Name & Description

`addEventListener(type, listener, useCapture)`
Register an event handler to a specific event type on the element.

-

All

`appendChild(appendedNode)`
Insert a node as the last child node of this element.

Node

All

`blur()`
Removes keyboard focus from the current element.

-

HTML, XUL

`click()`
Simulates a click on the current element.

-

HTML, XUL

`cloneNode(deep)`
Clone a node, and optionally, all of its contents.

Node

All

`compareDocumentPosition(otherNode)`

Number

All

`dispatchEvent(event)`
Dispatch an event to this node in the DOM.

Boolean

All

`focus()`
Gives keyboard focus to the current element.

-

HTML, XUL

libraries

libraries (eg, JQuery)

- › remove platform dependences
- › smooth over some non-uniformities

JQuery elements

- › JQuery wraps DOM elements
- › can't apply standard DOM calls

```
elt = document.getElementById("navbar");
elt.className = elt.className + " active"
```

in standard API

```
elt = $("navbar");
elt.addClass("active")
```

in JQuery

MIT OpenCourseWare
<http://ocw.mit.edu>

6.170 Software Studio
Spring 2013

For information about citing these materials or our Terms of Use, visit: <http://ocw.mit.edu/terms>.